



Big Dutchman
Innovation Breeds Success

BROILER MANAGEMENT







PAN FEEDING



FLUXX Broiler Feeder

The patent pending **FLUXX** broiler feeding pan system with **FX2** dish continues to set the standard in broiler feeding technology. The FLUXX system has been farm tested around the world, and has proven to be the best at faster starts and bigger birds.

The 14" pan allows for more feeding space, while the 16 arm design reduces feed waste and the 360° flood provides a consistent distribution of feed for easy access by your birds.

When a flooding pan is no longer required, simply winch the feeders off the floor and the feed adjust returns to the preset grow-out position. In the grow-out position the feed volume per pan is reduced.

Each pan has the feature of a feed saver lip and fins which work together to reduce waste, and the 360° rotation of the feeder insures even feed distribution.



3 DAY OLD CHICKS



FULL GROWN BROILERS



Internal lip is designed to give big birds easy feed access without wasting feed or injuring birds.



Feed levels are easily set with our "Spin'n lock" adjustment.

Preset grow out adjustment is returned as soon as the system is winched off the litter, reducing labor.



Swinging pan yields less bird injury and is easy to clean. Simply spray clean, open the bottom and let dry.



Snap on top cap for easy installation and service, saving time and maintenance costs.



Additional dish latch to ensure the dish stays secured to the pan assembly.



TRUflood™ 360° high feed level flooding allowing feed accessibility from day one.



Up to 16 feed stations encourages the birds to eat straight into the pan.



Pan spins 360° providing even feed distribution in the pan.



Heavy duty plastic construction creates a system that will last for years with minimal maintenance.

FEED DELIVERY

Every element of Big Dutchman's feeding system is designed for optimal performance and durability.



FEEDER AND HOPPER UNIT:

- Galvanized steel and heavy-duty plastic available
- Permanently lubricated, sealed bearings give the unit an exceptionally long life
- Removable 165lb plastic hopper extension allows the unit to be winched up until the feeder reaches the desired height for easy clean-out
- Lower limit hopper switches ensure feed availability at startup



AUGER AND TUBE:

- Constructed of heavy-gauge, steel with smooth flighting for long tube life and high energy efficiency
- Heavy-gauge construction of the tube prevents twisting, wear, and feed entrapment
- Feed drop-out holes handle most types of feed with no separation of ingredients



DRIVE UNITS:

- The POWERDRIVE motor features enhanced reliability with a **2 year warranty**
- High speed gear boxes (657 RPM) ensure rapid feed delivery
- Micro-switch control pan for consistent run times



STABILIZER HANGER:

- Stabilizer hanger prevents feed lines from rotating



PROXIMITY SWITCHES:

Proximity sensors for the detection of the feed level in hoppers, feed pans, bins, or for the control of poultry feed lines. Our sensors are customizable to adjust the desired time delay and sensitivity settings.



DRINKING SYSTEM



To achieve optimum performance from your birds, it is extremely important to provide fresh and clean drinking water. A reliable water supply free from contamination and within easy reach of the birds must be available. Big Dutchman satisfies all these requirements through a wide range of drinking systems for broilers, turkeys, breeders, as well as for pullets and layers.

- Nipple drinkers with and without drip cup
- Round drinkers for open water
- Anti-roost without electricity
- Double wire hanger
- Flipper

The choice of the right drinking system depends on the type of birds and your individual requirements.

In modern poultry production, nipple drinker systems have proven to be reliable and hygienic for supplying drinking water. They can be composed of the following parts:

- Pressure control unit with rinsing system - end or central supply, depending on the drinker length
- Slope regulator - evens out 4 – 6 inch incline
- End kit or end kit with automatic flush kit (optional) each with water level indicator
- Standard pipe with valve. Under normal operation the valve is open to allow the air to escape
- Aluminum extrusion or conduit with anti-roost wire
- Nipple tube with all stainless nipples and combi-nipples
- Suspension system





WATER FILTERING/MEDICATING SYSTEM:

A clean water supply is essential to achieve optimal performance and long service life from any nipple drinking system. The Water Filtering/ Medicating System ensures that the quality of the water being delivered is beneficial and makes it easy to administer medications by way of the medicator.

AUTOMATIC FLUSHING SYSTEM:

With the automatic flushing system you can rest assured that your drinking system will always be rinsed and replaced with fresh water whether you think about it or not.

The AutoFlush Controller opens and closes a solenoid valve allowing the system to automatically flush itself. The solenoid valve kit comes completely pre-assembled to the regulator making installations quick and easy. The Automatic Flushing System can also be adapted to existing installations.



OPTIONAL MINIDRINKER:



Optional MiniDrinkers are available as supplemental watering if required by integrator's production specifications.



FEED BINS

Reliable Big Dutchman components make the system complete, with bins and accessories for hygienic feed storage

The new series of feed hopper bins are now available in 3 standard sizes of 6, 9 and 12 feet in diameter. Each of the 3 sizes is available in 1 - 4 rings. The 12' bin is also available with 5 or 6 rings.

The bins are designed to store flowable, noncorrosive material with 50 pound/cubic foot (800.9kg/m³) bulk density.


FLEX-VEY® AUGER FILL SYSTEMS:

- Carry feed from feed bins to the house, moving up to 17,000 lbs. of feed per hour
- Single or tandem bin installations and single or double systems
- Customized to meet your needs
- High quality and extremely flexible spring steel
- Feed can be transported into the house around bends of up to 90° safely, quickly and without feed separation
- Universal application for each type of house
- High conveying capacities
- Fast and easy assembly
- Can be V-belt motor driven or by a gear motor



CONVENIENT AND SECURE ACCESS:

Big Dutchman feed bins feature the exclusive, patented Auto-Lok ground control access system for opening, closing and latching the fill cap safely and easily from the ground. Our cap system comes completely factory assembled, saving significant time and trouble in installation.



The cap swings open a full 180° to lie flat and parallel to the ground, completely eliminating the annoying and all-too-frequent interference with, or damage to, the cap from the fill auger. To meet consumer demand, the fill cap is also available as a replacement for destroyed or damaged caps for most bins from other manufacturers.

FEED WEIGH SCALES:

- Dependable, accurate scales for outside use
- Available in capacities of 5,000 lb. and 10,000 lb.
- Scale, feeder, and extension combination offers an alternative feeding system used inside the building



DRIP LIP:

Big Dutchman's drip lip water deflection system is a one-of-a-kind, roll-formed bottom sheet edge. It forces water away from the hopper and lower boot area, giving complete weather protection without a loss in capacity.




BIN ROOF:



40° roofs provide additional strength and capacity

Big Dutchman offers your choice of a 30° or 40° bin roof to adapt to any application. Roof panels are precision manufactured using die-form tooling to provide consistent quality.

Both 30° and 40° roofs feature reinforcing ribs at each roof seam for added strength and rigidity.




Reinforcing Rib

HOPPER BOTTOMS:




Bin hoppers are available in three slopes: 45° for dry, free flowing grains and 60° or 67° for harder flowing feed.

By fitting snugly into the offset outward throat of the hopper, the heavy gauge galvanized steel collar provides a perfectly smooth internal transition for optimal product flow, as well as a sure-fit adapter for all 16" (406mm) unloading accessories. Hoppers are available at no additional cost with an optional 22" (559mm) opening, which adapts to our rotary unloader or the larger, heavy duty 22" (559mm) metal boot.




The eave is exclusive to our hoppers. The eave is the upper edge where the hopper is joined to the sidewall and is specially die-formed to conform to the shape of the sidewall corrugation (See figure A at left). Most other manufacturers depend on crimping and bolt pressure to force the connection (See figure B at left). This produces corrosion-prone distortion and dimpling of the sidewall. Big Dutchman die-formed eave provides a much tighter seal and smoother flow of material.

SURE-FLO:



Sure-Flo directs feed down the hopper of the bin rather than down the center, creating a first in, first out feed flow. The gentle movement of the heavy walled molded cone enhances flow as feed passes over it.

The Sure-Flo support bracket bolts to the hopper collar of new or existing feed bins and is quick and simple to install.



With Sure-Flo

Without Sure-Flo

TITAN CORROSION RESISTANT HIGH VOLUME TUNNEL FANS



A flush mount fiberglass housing design allows for long lasting durability against the harshest environments, along with easy installation for new construction or for updating existing poultry houses.

All internal fan components are made from stainless steel, aluminum, or metal that has been through a high temperature painting process. These rugged components are added to a newly engineered blade assembly consisting of three cast aluminum blades that are secured to a cast aluminum hub.

The HDPE damper doors and poly cone allow for less airflow restriction than other fans on the market, while at the same time giving you complete protection against the elements of "mother nature". The innovative drive assembly applies power through the belt directly to the propeller.

The blade load is concentrated over the bearings for more economical operation and longer bearing life.


The TITAN 54" is available in 1hp or 1.5 hp options along with 3 phase availability and is ready to be packaged in your next Big Dutchman poultry project.



				Cubic Feet per Minute (CFM) at Static Pressure												
Fan Model	BESS Lab Test #	Motor HP	Fan RPM @ .05"	0" S.P.		.05" S.P.		.10" S.P.		.15" S.P.		.20" S.P.		.25" S.P.		Air Flow Ratio
				CFM	CFM/Watt	CFM	CFM/Watt	CFM	CFM/Watt	CFM	CFM/Watt	CFM	CFM/Watt	CFM	CFM/Watt	
Exterior Mount FG Fan with Damper Door Discharge Cone & Guards																
TITAN 54L	16344	1	548	29,800	31.3	27,800	26.7	25,500	22.9	23,100	19.7	20,400	16.9	17,200	14.4	0.73
TITAN 54M	16346	1.5	592	32,200	27.2	30,400	23.9	28,300	21.0	26,200	18.5	24,000	16.3	21,100	14.2	0.79
TITAN 54L Δ	16343	1	554	30,100	33.5	28,100	28.9	26,000	24.9	23,700	21.5	21,200	18.6	18,100	16.0	0.75
TITAN 54M Δ	16340	1.5	595	32,500	29.6	30,800	26.1	28,700	22.7	26,700	20.1	24,300	17.6	21,600	15.4	0.79
TITAN 54N Δ	16342	2	625	33,900	26.1	32,100	23.2	30,300	20.7	28,300	18.5	26,200	16.4	24,100	14.7	0.82
TITAN 54EN Δ	16341	2	666	36,200	23.3	34,600	21.0	32,700	18.8	30,900	16.9	29,000	15.4	26,700	13.8	0.84

Δ -3-Phase Units

52" AND 54" GALVANIZED FANS



NEW DESIGN REDUCES MAINTENANCE COST

- A corrosion resistant belt tensioner reduces maintenance and provides continuous strong performance
- Long lasting, high quality, rubber belt is easily accessible
- New tie-bar shutter design provides smooth, quiet operation and cleans easily

LOW COST INSTALLATION

- Fan supplied completely assembled, ready to mount in the wall
- Single phase units supplied with 10 foot cord and molded plug
- Every fan is bench tested prior to shipment, preventing start-up delays

GALVANIZED SLANTWALL FANS FEATURES:

- Long lasting galvanized steel housing
- High efficiency dual voltage, single and 3 phase motors
- Belt drive fans provided with high quality rotary belt tensioner
- Strong stainless steel shutter frame with PVC louver and tie-bar
- Easy to remove, high quality rubber belt
- Cast iron, greaseable air handling bearings

Fan Model	Fan Size	Motor HP	Fan RPM	CCFM	CCFM/Watt	Thrust, lbf	Thrust Eff., lbf/kW
NBCB52L	52	1	481	33,598	28.6	24.7	21.0
NBCB52M		1 1/2	553	38,890	22.8	33.3	19.5
NBCB52N Δ		2	589	42,148	21.4	38.6	19.6
NBC54L	54	1	452	38,014	32.3	27.8	23.6
NBC54M		1 1/2	485	40,657	29.4	31.8	23.0
NBC54N Δ		2	535	44,852	24.2	38.7	20.9

Δ – 3-Phase Motor



RAINMAKER 2 EVAPORATIVE COOLING

- Hygiene optimized: use of high-pressure cleaners possible to wash off dirt or deposits
- Standard pads are 6" thick, 23-1/2" wide
- Length options: 3', 4', 5', 6', 7' and 10' (other sizes on request)
- Weight: 2.25 lbs /sq ft (11 Kg/m²)
- Operating range: from -4°F to 176°F (-20° C to +80°C)
- UV - resistant
- Recyclable
- Plastic cooling pads require a high volume of water, Big Dutchman highly recommends the use of these pads exclusively with its RainMaker 2 system. Use of these pads in any other cooling system may severely limit performance. Plastic pads weigh more than cellulose pads and therefore require additional support.
- This product has a cooling performance that is inherent to this type of technology. The manufacturer neither claims nor warrants that its performance is comparable to any other cooling technology.

Plastic pad option



ZEUS LED

Professional LED ceiling lamp

A customized lighting concept significantly contributes to the success of your farm. The ZeusLED evenly illuminates all areas of a poultry house, and is offered as a 1 or 2 channel lamp, which is an exclusive brand product.

ZeusLED can be used for multiple purposes due to the LED technology and a wide optical spectrum. Energy savings of up to 50 percent compared to conventional moisture-proof lamps are an unbeatable advantage.



- LED technology allows for long-lasting energy savings of up to 50%
- 0 to 100% dimmable
- Zero flickering even at low light intensities
- Wide optical spectrum from warm white to cool white, infinitely variable
- 2 - channel moisture-proof LED lamp, e.g. to simulate sunrise and sunset
- Modular design consisting of a power supply unit, an LED driver and LED lamps
- Long service life of 50,000 hours and low maintenance requirements
- Rugged aluminum housing with an ingress protection rating of IP 65
- Exterior heat sink for optimum cooling
- Diffuser (optional) reduces dazzle effects, especially with low ceiling heights
- Can be installed at walls, ceilings or tubes

FLEX LED

The innovative and flexible LED tube lamp for any area of application

FlexLED is an innovative LED tube lamp which can be used in a variety of applications. Whether in aviaries or colony systems, there are few boundaries for FlexLED. The lamp is wired without connectors, requiring only one continuous main cable.

This allows easy installation of the LED tube in almost any space, and can be connected to the main cable where required. Retrofitting additional LED tubes at a later date is also very simple.



The LED tube is characterized by the following features:

- LED technology requires very low energy requirements, and has a long service life
- 0 to 100 % dimmable
- Even distribution of light due to the special profile of the housing
- Zero flickering even at low light intensities
- Available in four lengths: 1130, 1380, 1800 and 2340 mm.

THE ADVANTAGES AT A GLANCE:

- 48 V DC safety extra-low voltage
- IP 69K is resistant against high pressure cleaning
- Plug & play installation allows for quick, easy and flexible mounting
- Use of brand LEDs (Osram)
- Continuous main cable prevents contact resistance due to plug connections
- Good price/performance ratio

RADIANT BROODERS

SOLAIRE™ LOW PRESSURE BROODER



OPTIONAL ZONE CONTROL SYSTEM:

A power pack is available to provide automated battery back-up. Zone Control is available with Solaire™ single-jet or infrared brooders. The optional Zone Control System (24V AC/12V DC) electronically controls a group of brooders using one thermostat.


DIRECT SPARK IGNITION SYSTEM:

Direct spark ignition eliminates standing pilots and provides electronic control of a group of brooders. Direct spark ignition is available on single-jet and infrared brooder models. The system requires a transformer.

SIMPLE TO USE AND EASY TO CLEAN:


Assembling a Solaire™ brooder requires only a wrench and a screwdriver. The simplified control mounting eliminates bulky clips or wires, and the DSI box is sealed to allow for more protection and thorough washdowns.

TRU40 HIGH PRESSURE BROODER



FEATURES AT A GLANCE:

- Stainless steel emitter assembly, insulated and uninsulated – will not crumble or distort. Features 3-year limited warranty
- Stainless steel, corrosion resistant burner assembly features simple disassembly for easy cleaning and maintenance
- Stainless steel main burner gas line for strength and durability
- Large deep dish aluminum canopy to efficiently reflect heat to litter area where it's needed most
- Ignition Control features a moisture resistant enclosure
- Safety pan below burner helps shield litter area directly beneath brooder
- Low profile mounting bracket permits easy levelling of brooder
- No filter needed
- Ideal for replacement of existing high pressure brooders



RADIANT TUBE HEATERS

Our Radiant Tube heater provides a large, even heat footprint, promoting improved bird growth. Delivering a large, extra wide, rectangular heat pattern at litter level results in a more uniform heat distribution for your poultry house. Better brooding conditions means more comfort for your birds.

BIGFOOT TUBE HEATER



19° ANGLE OPTIMIZED REFLECTOR ANGLE:

- Better radiant throw
- Less convective wash
- Higher radiant output and more fuel efficient
- Faster to put heat on the floor
- Low clearances to combustibles above
- Unique U-bend reflector directs more heat from the end of the tube

HEAT PATTERN:

- Even temperature distribution
- Allows birds warm access to food and water
- 4" diameter tubes create large radiant surface to emit heat to the outside wall
- Bigger footprint than other competitive units


FUSION TUBE HEATER



TUBE INTEGRITY SAFETY SHUT-OFF SYSTEM

This system uses a simple principle to place an electrically insulated aluminum wire in tension above the reflector.

Low voltage is then continuously passed along the wire in line with the gas control circuit. If heat levels increase due to heat exchanger failure, the wire melts and the safety circuit is broken, breaking the 24 volt circuit and shutting down the heater.



- An energy efficient radiant heating system that saves fuel, reduces maintenance and permits higher mounting
- Calorized aluminized steel emitter tubes for corrosion resistance and greater radiant output
- Unique diagnostic monitoring lights show when heater is operating, and assists with fault diagnosis
- Ceiling stays cool – no need for insulated board above heater.**
- CSA design certified for safety

- Excellent radiant throw and even temperature distribution
- 4" diameter tubes create a large radiant surface to emit more heat over a wide rectangular area
- Each unit comes with fresh air intake kit, exhaust hood, stainless steel flexible gas connector and a pre-wired electrical connection
- Features a 3-year limited warranty on complete emitter assembly

**Provided minimum clearances-to-combustibles are maintained

ViperTouch

Climate and Production Computer - complete climate and production control for your poultry house... at your finger tips



The new ViperTouch is a state-of-the-art climate computer that allows you to control the entire house efficiently.

ViperTouch is a full production and management computer. It records all important data concerning production, growth, feed and water consumption, and mortality, allowing you to react quickly to changes and to take the required action resulting in better results.

The extension modules “full broiler functionality” and “full breeder functionality” provide additional functions which are especially important for broiler and broiler breeder management.

FEATURES AT A GLANCE:

- Simple operation via touch screen
- Ideal climate and production computer for all types of poultry production
- Adjustable operating modes: Basic, Flex or Profi Mode
- Speaks 16 languages – including yours
- Customizable home screen
- Integrated network interface
- Simple alarm management
- BigFarmNet-Manager with mobile and web access

FARMBOOK PRO

The first app for every broiler farmer!


Documenting and analyzing your production results will be as simple as never before

MOBILE RECORDING:

Always have FarmBookpro at hand with your smart-phone, wherever you are.

COMPATIBLE WITH ANY EQUIPMENT:

Whether you have installed an advanced control system or a simple computer, recording and viewing your production data is incredibly easy, and the equipment brand makes no difference.



ONLINE AND OFFLINE USE POSSIBLE:

All data you record is transferred to the FarmBookpro website, either in real time or whenever your smart-phone can connect to a network.

MULTIPLE HOUSES / LOCATIONS INTEGRATION:

Manage as many locations and houses as you want.

AS MANY ACTIVE USERS AS YOU NEED:

Add your staff to FarmBookpro simply by entering an e-mail address. Users can record data independently and simultaneously, and all their inputs are traceable.

GOOD OVERVIEW DUE TO GRAPHS:

The FarmBookpro website has easy to read graphs, which helps you compare your current values with breeder recommendations or previous batches.

WITH PICTURE AND NOTES FUNCTION:

Record and archive feed deliveries simply by taking a photo of the delivery note. Use digital notes to describe technical issues and to document abnormalities in the flock so you can immediately forward them to your staff.

PDF OVERVIEW AT THE PUSH OF A BUTTON:

Based on the data you and your staff recorded, FarmBookpro will automatically create batch reports and generate a PDF overview you can print out or email.

DOL53 AMMONIA SENSOR

The first NH₃ sensor for continuous measuring of the ammonia concentration in the house air

DOL 53 provides exact figures on the NH₃ concentration in the house air at all times so you can immediately take suitable measures to reduce the ammonia content when necessary, because only healthy animals can show their full potential!

DOL 53 permanently monitors the ammonia concentration in the house air, allowing the house climate to be controlled based on the sensor's measurements. Our ViperTouch climate computer can receive and process the data provided by the sensor to regulate the house climate according to the measured values.

FEATURES AT A GLANCE:

- Exact and continuous measuring of the NH₃ concentration in the house air
- Measuring range covers concentrations typical for livestock production
- Easy integration into existing houses and their climate control systems
- Robust and reliable
- Easy to install
- Analogue 0 to 10 V output



SWING 20 BIRD SCALE

Precision weighing systems for all types of poultry – mobile or fixed installation

Monitoring bird weights is an important tool in modern poultry management. Especially in poultry growing, the exact determination of bird weights is a decisive factor for economic success.

Versatile poultry scale

Swing 20 consists of a load cell and a platform made of plastic material (or, as an option, stainless steel).



MAIN ADVANTAGES

Using the telescopic suspension, the platform can easily be adjusted in height and thus be adapted to the birds' age. The birds accept the scale well, resulting in plenty of weighings and therefore precise weight data.

Swing 20 is suspended from the barn's ceiling. During the service period, the scale can easily be removed for cleaning while the weighing electronics remain installed close to the ceiling where they are protected against dirt.





Big Dutchman
Innovation Breeds Success

Big Dutchman USA & Canada

3900 John F. Donnelly Dr. - Holland, MI 49424
Tel. +1 616 582 4000 - Fax +1 616 392 6188
bigd@bigdutchmanusa.com
www.bigdutchmanusa.com

Big Dutchman Latin America

10130 Perimeter Pkwy, Ste. 420 - Charlotte, NC 28216
Tel. +1 704 264 1660 - Fax +1 704 264 1661
www.bigdutchmanusa.com

Details are subject to change: 1/2019
86-00-7731